

**BOQ FOR INTERIOR FURNISHING WORK AT KGB AURAD BRANCH**  
**TQ AURAD & DIST. BIDAR**

<b>SI No</b>	<b>Description of Item</b>	<b>Qty</b>	<b>Unt</b>	<b>Rate in Rs</b>	<b>Amount in Rs</b>
<b>1</b>	<b>WOOD FRAMED PARTITION</b>				
	Providing and fixing of partly glazed double skin partition using 3" X 1.5" OR 2.25 X 2" SALWOOD sections for frame work with verticals at a maximum spacing of 3 ft. c/c and five horizontals at 0', 2', 7' false ceiling level & top. The partition shall be covered by 6 mm thick plywood on both sides for the bottom and the top panel. The finishing shall be with 1mm thick lamination of approved shade on both sides. The middle 5ft panel shall be covered by 6 mm thick plain glass with necessary TW beadings. The glass panel shall have designed artistic etching frosting. There shall be a 4" height skirting on both sides by using 12 mm commercial plywood with 1mm lamination finish. Necessary openings for the door shall be provided with TW beadings which shall be deducted from the payable area. In specified locations like UPS Room, Record Room etc. the middle panel shall be fully covered with plywood as mentioned above, if required by the Bank, Manager Cabin shall be with maximum glass area as required at site condition.	409	SFT		
<b>2</b>	<b>WOOD FRAMED PARTLY GLAZED DOOR</b>				
	Providing and fixing of double skin door shutter using 3" X 1.5" SALWOOD section for the two vertical and three horizontals. The two sides shall be covered by 6 mm thick commercial plywood. The finishing on two faces shall be with 1mm thick lamination of approved shade on both sides. An opening of size 2 ft x 5ft shall be provided with 6mm thick plain glass with designed artistic etching, frosting and fixed with T. W beadings. All the exposed edges shall be provided with T. W beading of appropriate width and 1/2" thickness. All the exposed edges T.W beadings shall be finished with two coats of wood polish over a coat of primer. The door shutter shall be fixed with 4 No.s of 6" length brass hinges and approved design stainless steel handles. The size of the door shall be 7 ft x 3 ft.	3	NO		
<b>3</b>	<b>DOOR CLOSURE</b>				
	Providing and fixing DOOR closure to the wood framed door shutter.	3	NO		
<b>4</b>	<b>NOTICE BOARD</b>				
	Providing and fixing of Notice board of size 3'x2' by using 19mm commercial block board with 1 1/2" x 1/2" TW beading around. The inside surface shall be provided with 12 mm thick soft board with fabric on the top. The TW beading shall be provided with 2 coats of polish over a coat of primer.	1	NO		
<b>5</b>	<b>CUSTOMER WRITING DESK(FREE STANDING TYPE)</b>				
	Supplying and fixing customer writing desk with top, front, side supports and foot rest with necessary bins of size 6" x6" ( front opening) for keeping challans, all made out of 19mm commercial block board. The top, front and side surfaces laminated with 1mm lamination and remaining surfaces neatly painted with 2 coats of synthetic enamel paint over a coat of primer. 2 No's Dst Bin of size also be provided with design beading opening on top and side doors with nob. The overall size shall be 2'x3'x3 1/2(DXWXH).	1	NO		

6	<b>VIKET GATE</b>	1	NO		
7	<b>GLASS PARTITION FOR CUSTOMER COUNTER</b>	50	SFT		
8	<b>CASH COUNTER ALUMINIUM JALI PARTITION</b>	35	Sqft		
9	<b>KEY BOARD TRAY</b>				
	Providing & fixing of KEY BOARD tray of size 24"x12"x1" using 18mm commercial block board for the bottom with alround support of 1"x 1/2" TW beading. The inside surfaces of the tray shall be finished with 1mm thick lamination. All the exposed TQ beadings shall be provided with two coats of polished over a coat of primer. The key board shall be fixed to the counter with Telescopic Channel. All non laminated exposed surfaces except TW shall be provided with two coats of enamel paint over a coat of primer 'THE KEY BOARD SHALL BE FIXED TO THE DIFFERENT ITEMS LIKE COUNTERS, TABLES.'	7	NO		
10	<b>CASH COUNTER</b>				
	Providing & fixing High level individual cash counter of length 60" total height 45" customer top width 16" and working top width of 36" width (all minimum dimensions) all as per drawing with front working top, customer top, main vertical side support upto the customer top, and intermediate vertical support for draw unit upto working top. The working top shall be at a height of 36" and customer top at height of 45" above floor. There shall be three draws of size 13.5"x22"x5" (internal dimensions) fixed inbetween the intermediate support and main side support. The portion below the draws shall be a cupboard with front shutter. The counter and the draws shall be made by using 19mm commercial block board except for draw bottom which shall be provided with 6mm commercial plywood. The front elevation of the counter shall be as per the design detailed in the drawing of front office counters (item 21 below) using 6mm thick MDF to provide recessions as required at site condition be powder. The working top, customer front, top, front face of shutter and draws shall be finished with 1 mm thick lamination & provided with 10mm clear glass polished edges biveled. There shall be shelf of size 10" x 20" below the working top of CPU UNIT using 19mm commercial block board. A foot rest of 3" x 1 1/2" hardwood section shall be provided. The draws shall have sliding arrangement with readymade metal slides and metal rollers. All the exposed edges shall be provided with teak wood beadings of size 1" x 1/4" POLISHED . All non laminated exposed surfaces shall be provided with two coats of enamel paint over a coat of primer. Each draw shall have one multipurpose concealed lock and stainless steel handle. Necessary openings for the access of the wires with plug shall be provided with PVC caps.	1	No		
11	<b>FRONT OFFICE CUSTOMER COUNTER</b>				
	Providing & fixing Running customer counter of total height 39", customer top width 6" and working top width of 30" width (all minimum dimensions) all as per drawing with front, working top, customer top, main vertical support upto the customer top at every 5ft c/c and intermediate vertical support for draw unit upto working top. The working top shall be at a height of 30" and customer top at a height of 39" above floor. There shall be two draws of size 13.5" x 22"x 5"(internal dimensions) fixed in between the intermediate support and main support at every 5ft C/C. The portion below the draws shall be a cupboard with front shutter. The counter and the draws shall be made by using 19mm commercial block board except for draw bottom which shall be provided with 6mm commercial plywood. The front elevation of the counter shall be as per the design detailed in the drawing using 6mm thick MDF to provide recession and finished with TQ beading 1mm lamination. The customer top, working top, customer front & front face of shutter and draw shall be finished with 1 mm thick lamination. The customer hood shall have a curver profile as per the drawing. The working top, customer top shall be provided with 10mm polished clear glass edges biveled. There shall be shelf of size 10" x 20" below the working top for CPU UNIT using 19mm commercial block board as shown in the drawing. A foot rest of 3" x 1 1/2" hardwood section shall be provided. The draws shall have sliding arrangement with readymade metal slides and metal rollers. All the exposed edges shall be provided with teak wood beadings of size 1" x 1/4" POLISHED . All non laminated exposed surfaces shall be provided with two coats of enamel paint over a coat of primer. Each draw shall have one multipurpose concealed lock and stainless steel handle.Necessary openings for the access of the wires with plug shall be provided with PVC cap				
12	S.	24	RFT		
12	<b>MANAGER TABLE</b>				

Providing & fixing TABLE of length 72", height 30" and top width 36" all minimum dimensions with front working top and side support. There shall be three draws of size 13.5"x22"x5" fixed in a alround boxing with top and one of the side of the tables as common top and side. All by using 19mm commercial block board except for draw bottom which shall be provided with 6mm commercial plywood. The front elevation of the tables shall be as per the design detailed in the drawing using 6mm thick MDF to provide recession and finished with TW beadings, 1mm thick lamination. The working shall be provided with 10mm thick polished clear glass with edges biveled. There shall be shelf of size 10"x20" below the working top for CPU UNIT using 19mm commercial block board as shown in the drawing. A foot rest of 3" x 1 1/2" hardwood section shall be provided. The draws shall have sliding arrangement by Telescopic Channels. All the exposed edges shall be provided with teak wood beadings of size 3/4" x 1/4". All non laminated exposed surfaces shall be provided with two coats of enamel paint over a coat of primer. Each draw shall have stainless steel handle with a centralized locking system for the three draw unit. Necessary openings for the access of the wires with plug shall be provided inclusive of working top and covered with PVC caps				
	1	No		
13 <b>Cheque Drop Box</b>	1	No		
14 <b>Suggestion Box</b>	1	No		
15 <b>False Ceiling</b>	90	SFT		
16 <b>Vertical Blind</b>	75	SFT		
17 <b>Godreg Lock for Doors</b>	3	NO		
<b>Total (Amt excl. of GST)</b>				