BOQ FOR FURNISHING WORKS OF MANDIKAL BRANCH, KARNATAKA GRAMIN BANK, MANDIKAL. KOLAR DISTRICT.

GENERAL MAIN SPECIFICATION SHALL BE CONSIDERED FOR ALL ITEMS.

The Commercial boards used should be made of 19mm MR grade commercial board with both or single side 31mm thick laminated finish. Ply wood used for Storage unit rear side, partion wall inner and outer side and drawer and cupboard bottom which shall be provided with 6 mm MR grade commercial plywood with finish with 1mm thick laminate on one side per sheet. The boards and laminate make and colours for the counter, table top, vertical sides, drawer, cupboard, storage unit, bands, skirting, partion wall customer writing table, Notice board, Suggestion box etc shall be strictly as per the recommended brand and colours indicated by Bank. The hidden surfaces to be painted with one coat of wood primer and two coats of enamel painting of approved colour and make of the paints. All the exposed edges shall be lipped with 1"X0.5" matching Teak Wood Beading & neatly polished with proper number of coats of melamine polish shall be provided. Tables and counters shall be provided with required no of round holes of 2.5" size with PVC cap at the required location for wire management etc. complete, Tables and counters shall be provided with two drawers minimum size of 13.5"x 22"x 5" (internal dimensions) fixed in between the intermediate support and main support, at every maximum of 5 ft c/c. main supports are provided for each counter and cusstomer side covered upto table top with Commercial boards used should be made of 19mm MR grade commercial board with both or single side side 1mm thick laminated finish, the portion below the drawers shall have a cupboard with front shutter, providing and fixing 100mm 'C' type stainless steel handles, multipurpose locks, automatic steel Zero crank hinges for cupboards, the drawers to be provided with sliding channels etc. For every seating area tables and counters there shall be a key board tray of minimum 21" x 18" size made of 19mm MR grade commercial board with both side 1mm thick laminated and fixed with telescopic type metal channels fixed on the lower side of the counter/table top. For every seating area of tables and counters a foot rest of 3" x 2" Seasoned hard wood section with proper no of coats of melamine polish shall be provided on the lower side of the counter/table top. The front elevation of the counter, partition wall shall be as per the design detailed in the drawing or as detailed by the Architect/ Engineer in-charge using the front elevation of the counter / partion shall be as per the design detailed in the drawing using 6mm thick design teak wood/MDF material to provide recession and finished with laminate & 1mm thick laminate. Handles and other hardware items and other items have to be used as per banks approved list of material/ banks prior approval, etc.complete. The rate quoted should include cost and conveyance of all materials, labour for all items of work, HOM as per specification. rest of specifications same as MAIN specifications of all items, including tax, Complete to the satisfaction of the Engineer / Bank as per design/ drawing enclosed.

NO	DESCRIPTION OF ITEM OF WORKS	UNIT	TOTAL QTY	RATE	AMOUNT
1	CASH COUNTER TABLE				
	Providing and fixing Cash Counter Table as shown in the Drawing. The counter shall have overall size of 2° 6" (W) x6°0" (L) x 2° 6" (H) working top with customer transaction top at an height of 42" & the working counter top at 30" height from floor level. The customer transaction top shall have a customer ledge of width 6" (towards customer side) & 12" width ledge towards cashier side,made of 19mm MR grade commercial board with both side 1mm thick laminated finish all as shown in the drawing. There shall be two drawers of size 13.5"x 22"x 5" (internal dimensions), at every maximum of 5 ft c/c. main supports are provided for each counter and customer side covered upto table top with Commercial boards used should be made of 19mm MR grade commercial board with both or single side side 1mm thick laminated finish, On top of cash counter table attach to front partition wall 4 no. of cash boxes to be provided to keep different denomination notes. The portion below the drawers shall have a cupboard with front shutter. The working top, customer top, main vertical side and drawer and cupboard sides support shall be made out of 19mm MR grade commercial board & finished with 1mm thick lamination on all visible sides except for draw bottom which shall be provided with 6 mm MR grade commercial plywood. All the exposed edges shall be provided with wood beadings of size 1" x .5" with proper polish For every seating area there shall be a key board tray of minimum 21" x 18" size, a foot rest of 3" x 2" Seasoned hard wood section with polish. The counter and the drawers shall be made by using 19mm MR grade commercial board with 1 mm thick laminate finish except for drawer bottom which shall be provided with 6 mm MR grade commercial plywood. The drawers to be provided with sliding channels including fixing keyboard with telescopic sliding channel. Inner portion of drawers, cupboards finished with internal lamination of 1mm thick of approved colour. The hidden surfaces to be painted, including providing and fixing 100mm fC' type				
	1. 1NO X 4.33' X 2.5'				
	ITEM TOTAL QUANTITY	Sqft	10.83	1 1	

Providing and fixing partition for cash cabin front by using 2.5°5.2.5' size well separed from the document of the class quality of all hollochies and verticals. There shall be altered three hindrochies at 0° 0.0°8° and 35° levels [sparod] from the custioner counter top level (which we have any counter upon 7° it height and one up to customer counter top level.) The Partition shall be askined on both ficases with 6 mm. MR grade commercial phywood of approved brand termite and water resistant. Exercise ficas to be pasted with mm thois laminate of approved quality 8 Colour to the totation Partie of the Partition. The middle 00° height pened to the counter bendings, word, public bendings, all the estimations are still be provider conted with approved colour. At the mid portion of the middle panel them shall be an opening of 0° x 0° with around firem work 8 in level, pening shall have a stilling or openable by pre-shuffer with looking arrangement from made to facilitate cash receiving pening. The top panel shall be bendings after the middle panel to be covered by alternativing reflicit and the provision of exist fame was an excession of the provision of exist fame was an excession which are the pasted of the provision of exist fame was as a receivant with looking arrangement from made to facilitate cash receiving pening. The top panel shall be bending after the middle panel to be covered by alternativing reflicit and the provision of exist fame was as a receivant with a familiar pening of the provision of exist fame was as a receivant with a familiar pening and the provision of exist fame was as a receivant with a familiar pening and the provision of exist fame was as a receivant pening from the floor interest the provision of exist fame was as a receivant pening of the pening and the provision of exist fame was a familiar pening and the pening of the pening pening pening pening and the pening pening pening pening pening from the floor level. There shall be a horizontal was a familiar pening pening pening from the				
3 PARTITION FOR CASH CABIN SIDE & BACK Providing and fixing partitions for cash cabin sides & rear areas by using 2.5"x2.5" size well seasonedhard wood sections of first class aquality for all horizontals and verticals, spaced at required intervals but not more than 3 feet of: unless otherwise specified. There shall be atleast 4 horizontals wood sections at 0" 0", 2"0", 3"8" and 70" levels [aprox] from the floor level. There shall be vertical supports for every maximum of 3 feet interval or part thereof unless otherwise specified. The bottom 3"6" height of Partition shall be skinned on both faces with 6 mm. MR grade commercial plywood. of approved brand termite and water resistant. Exterior faces to be pasted with 1mm thick laminate of approved quality & Colour to the bottom Panel of the Partition, The top remaining panels shall be covered by 7.5 mm thick 56mm x 47mm opening aluminium grill (AL 101) fixed with suitable corner beadings, rubber beadings. All the aluminium sections shall be powder coated with approved colour. There shall be a horizontal tray at 3 ft level to facilitate slips movement and communication between superviser and cashier. The top panel Above Counter shall be covered by glass panels made of 12 mm thick plain glass fixed with necessary beedings. The approximate size of the Bulk Cash Cabin is4"6" (width) x 9" (length) x 7"0" (height). The partition shall have 1 No. of Door with Size 0.75m x 2.1sm with Proper Hinges, Stoppers Locks, Handles, Hydraulic Closure etc., complete. Necessary openings must be made in the frame sections to run the wires, computer cables wherever necessary with Proper Hinges, Stoppers Locks, computer Information outlets, making provision for slaying conduit. The rate include Provision of extra frame work as necessary verticle and horizantal members to be taken upto flooring joined with a horizontal members at top and for skirting, etc. complete. The general main specification, make, colour, of Items, quantity of Items, material of Items (hitch Stimm x 47mm aluminium	wood sections of first class quality for all horizontals and verticals. There shall be atleast three horizontals at 0' 0', 0'8" and 3'3" levels [approx] from the customer counter top level (which will be at 42 inches height from floor level). There shall be vertical supports on two ends of the cash counter upto 7 ft height and one up to customer counter top level. The Partition shall be skinned on both faces with 6 mm MR grade commercial plywood of approved brand termite and water resistant. Exterior faces to be pasted with 1mm thick laminate of approved quality & Colour to the bottom Panel of the Partition, . The middle 0'8" height panel to be covered by 7.5 mm thick 56mm x 47mm opening aluminium grill (AL 101) fixed with suitable corner beadings, wood,rubber beadings. All the aluminium sections shall be powder coated with approved colour. At the mid portion of the middle panel there shall be an opening of 6" x 6" with alround frame work & this opening shall have a sliding or openable type shutter with locking arrangement from inside to facilitate cash receiving/ paying. The top panel shall be covered by glass panes made of 12 mm thick plain glass fixed with necessary wood,rubber beadings & the middle panel to be covered by aluminium grill (AL 101) fixed with suitable corner beadings. The glass panel shall have designed artistic etching using frosted film. The rate include Provision of extra frame work as necessary verticle and horizantal members to be taken upto floor joined with a horizontal member at top and for skirting,etc. complete. The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading, fittings, hardware items, paintings, wood polish,			
3 PARTITION FOR CASH CABIN SIDE & BACK Providing and fixing partitions for cash cabin sides & rear areas by using 2.5"x2.5" size well seasonedhard wood sections of first class quality for all horizontals and verticals, spaced at required intervals but not more than 3 feet civ unless otherwise specified. There shall be effect of unless otherwise specified. There shall be extended supports for every maximum of 3 feet interval or part thereof unless otherwise specified. The bottom 3'5" height of Partition shall be skinned on both faces with 6 mm. MR grade commercial phywood. of approved frank femt and water resistant. Exterior faces to be pasted with 1 mm thick laminate of approved quality & Colour to the bottom Panel of the Partition, The top remaining panels shall be covered by 7.5 mm thick 56mm x 47mm opening aluminium gelicins shall be powder coated with approved colour. There shall be a horizontal tray at 3 ft level to facilitate slips movement and communication between superviser and cashier. The op panel Above Counter shall be covered by glass panels made of 12 mm thick plain glass fixed with necessary beedings. The approximate size of the Bulk Cash Cabin 145" (width) 3" (flength) x" ("height). The partition shall have 1 No. O Door with Size 0.75m x 2.13m with Proper Hinges, Stoppers Locks, Handles, Hydraulic Closure etc., complete. Necessary openings must be made in the frame sections to run the wires, computer cables wherever necessary with PVC cap. Similarly necessary cuttings to be made in the partition to fix withch boxes of electrical, telephone sockets, computer information outlets, making provision for laying conduit. The rate include Provision of extra frame work as necessary vertice and horizantal members to be taken uple flooring ioned with a horizontal member at top and for skirling.etc. complete. The general main specification shall considered for design, specification, shall be powder coade with approved colour. The general main specification shall considered for commercial by wood, lamination	1. 1NO X 4.33' X 5'			
Providing and fixing partitions for cash cabin sides & rear areas by using 2.5°x2.5° size well seasonedhard wood sections of first class quality for all horizontals and verticals, spaced at required intervals but not more than 3 feet of unless otherwise specified. There shall be attest 4 horizontal wood sections at 0° 0°, 20°, 36° and 70° levels [approx] from the floor level. There shall be vertical supports for every maximum of 3 feet interval or part thereof unless otherwise specified. The bottom 36° height of Partition shall be skinned on both faces with 6 mm. MR grade commercial plywood, of approved brand termite and water resistant. Exterior faces to be pasted with 1mm thick laminate of approved quality & Colour to the bottom 74° mm opening aluminium grill (AL 101) fixed with suitable corner beadings, rubber beadings. All the aluminium sections shall be powder coated with approved colour. There shall be a horizontal tray at 3 ft level to facilitate slips movement and communication between superviser and cashler. The top panel Above Counter shall be covered by glass panels made of 12 mm thick plain glass fixed with necessary beedings. The approximate size of the Bulk Cash Cabin s46° (with) x9 (length) x70° (height). The partition shall have 1 No. of Door with Size 0.75m x2.13m with Proper Hinges, Stopers Locks, Handles, Hydraulic Closure etc., complete. Necessary openings must be made in the frame sections to run the wires, computer cables wherever necessary with PVC cap. Similarly necessary cuttings to be made in the partition to fix switch boxes of electrical, telephone sockets, computer Information outlets, making provision for laying conduit. The rate include Provision of extra frame work as necessary verticle and horizontal member at top and for skirting,etc. complete. The general main specification shall considered for design, specification, shall considered for design, specification, shall considered for design, specification, make, colour, of items, quantity of items, material of items of commercial	ITEM TOTAL QUANTITY	Sq.ft	21.67	
Providing and fixing partitions for cash cabin sides & rear areas by using 2.5°x.25° size well seasonedhard wood sections of first class quality for all horizontals and verticals, spaced at required intervals but not more than 3 feet of unless otherwise specified. There shall be atleast 4 horizontal wood sections at 0°0 x.20°, 45° and 70° fevies[approx] from the floor level. There shall be vertical supports for every maximum of 3 feet interval or part thereof unless otherwise specified. The bottom 36° height of Partition shall be skinned on both faces with 6 mm. MR grade commercial plywood, of approved brand termite and water resistant. Exterior faces to be pasted with 1mm thick taminate of approved brand termite and water resistant. Exterior faces to be pasted with 1mm thick taminate of approved brand termite and water resistant. Exterior faces to be pasted with 1mm thick taminate of approved brand termite and water resistant. Exterior faces to be pasted with 1mm thick taminate of approved brand termite and water resistant. Exterior faces to be pasted with 1mm thick taminate of approved brand termite and water resistant. Exterior faces to the pasted with 1mm thick taminate of approved colour. There shall be a horizontal tray at 3 ft level to facilitate slips movement and communication between superviser and cashier. The top panel Above Counter shall be covered by glass panels made of 12 mm thick plain glass fixed with necessary beedings. The approximate size of the Bulk Cash Cabin s46° (width) x9 (length) x70° (height). The partition shall have 1 No. of Door with Size 0.75m x 2.13m with Proper Hinges, Stoppers Locks, Handles, Hydraulic Closure etc., complete. Necessary openings must be made in the frame sections to run the wires, computer cables wherever necessary with PVC cap. Similarly necessary cuttings to be made in the partition to fix switch boxes of electrical, telephone sockets, computer Information outlets, making provision for laying conduit. The rate include Provision of extra frame work as necessar	2 DARTITION FOR CASH CARIN SIDE & DACK			
2. 2NO X 7.96' X 7.5' ITEM TOTAL QUANTITY Sq.ft 154.38 4 ALUMINIUM GRILL FOR CASH CABIN TOP providing & fixing 7.5mm thick 56mm x 47mm aluminium grill (AL 101) at the top of the cash cabin with necessary teak wood beading. All the accessories used shall be concealed type. All the aluminium sections shall be powder coated with approved colour. The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading , fittings, hardware items , paintings, wood polish, rate etc. complete , Proper vertical & horizontal support required should be provided and same should be Fineshied with 1MM Laminate 1. 1NO X 4.67' X 8' ITEM TOTAL QUANTITY Sq.ft 37.33	seasonedhard wood sections of first class quality for all horizontals and verticals. spaced at required intervals but not more than 3 feet c/c unless otherwise specified. There shall be atleast 4 horizontal wood sections at 0" 0", 2"0", 3"6" and 7"0" levels [approx] from the floor level. There shall be vertical supports for every maximum of 3 feet interval or part thereof unless otherwise specified. The bottom 3"6" height of Partition shall be skinned on both faces with 6 mm MR grade commercial plywood. of approved brand termite and water resistant. Exterior faces to be pasted with 1mm thick laminate of approved quality & Colour to the bottom Panel of the Partition, The top remaining panels shall be covered by 7.5 mm thick 56mm x 47mm opening aluminium grill (AL 101) fixed with suitable corner beadings, rubber beadings. All the aluminium sections shall be powder coated with approved colour. There shall be a horizontal tray at 3 ft level to facilitate slips movement and communication between superviser and cashier. The top panel Above Counter shall be covered by glass panels made of 12 mm thick plain glass fixed with necessary beedings. The approximate size of the Bulk Cash Cabin is4"6" (width) x 9" (length) x 7"0" (height). The partition shall have 1 No. of Door with Size 0.75m x 2.13m with Proper Hinges, Stoppers Locks, Handles, Hydraulic Closure etc., complete.Necessary openings must be made in the frame sections to run the wires, computer cables wherever necessary with PVC cap. Similarly necessary cuttings to be made in the partition to fix switch boxes of electrical, telephone sockets, computer Information outlets, making provision for laying conduit. The rate include Provision of extra frame work as necessary verticle and horizantal members to be taken upto flooring joined with a horizontal member at top and for skirting, etc. complete. The general main specification shall considered for design, specification, make, colour, of items, quantity of items, material of items for commercial board, commercial p			
ITEM TOTAL QUANTITY 4 ALUMINIUM GRILL FOR CASH CABIN TOP providing & fixing 7.5mm thick 56mm x 47mm aluminium grill (AL 101) at the top of the cash cabin with necessary teak wood beading. All the accessories used shall be concealed type. All the aluminium sections shall be powder coated with approved colour. The general main specification shall considered for design, elevation, specification, make,colour, of items, quantity of items, material of items for commercial board,commercial ply wood, lamination, hard wood section, glass, beading, fittings, hardware items, paintings, wood polish, rate etc. complete, Proper vertical & horizontal support required should be provided and same should be Fineshied with 1MM Laminate 1. 1NO X 4.67' X 8' ITEM TOTAL QUANTITY Sq.ft 37.33	1. 1NO X 4.67' X 7.5'			
4 ALUMINIUM GRILL FOR CASH CABIN TOP providing & fixing 7.5mm thick 56mm x 47mm aluminium grill (AL 101) at the top of the cash cabin with necessary teak wood beading. All the accessories used shall be concealed type. All the aluminium sections shall be powder coated with approved colour. The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading ,fittings, hardware items ,paintings, wood polish, rate etc. complete , Proper vertical & horizontal support required should be provided and same should be Fineshied with 1MM Laminate 1. 1NO X 4.67' X 8' ITEM TOTAL QUANTITY Sq.ft 37.33	2. 2NO X 7.96' X 7.5'			
4 ALUMINIUM GRILL FOR CASH CABIN TOP providing & fixing 7.5mm thick 56mm x 47mm aluminium grill (AL 101) at the top of the cash cabin with necessary teak wood beading. All the accessories used shall be concealed type. All the aluminium sections shall be powder coated with approved colour. The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading, fittings, hardware items, paintings, wood polish, rate etc. complete, Proper vertical & horizontal support required should be provided and same should be Fineshied with 1MM Laminate 1. 1NO X 4.67' X 8' ITEM TOTAL QUANTITY Sq.ft 37.33	ITEM TOTAL QUANTITY	Sq.ft	154.38	
providing & fixing 7.5mm thick 56mm x 47mm aluminium grill (AL 101) at the top of the cash cabin with necessary teak wood beading. All the accessories used shall be concealed type. All the aluminium sections shall be powder coated with approved colour. The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading , fittings, hardware items , paintings, wood polish, rate etc. complete , Proper vertical & horizontal support required should be provided and same should be Fineshied with 1MM Laminate 1. 1NO X 4.67' X 8' ITEM TOTAL QUANTITY Sq.ft 37.33				
cabin with necessary teak wood beading. All the accessories used shall be concealed type. All the aluminium sections shall be powder coated with approved colour. The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading, fittings, hardware items, paintings, wood polish, rate etc. complete, Proper vertical & horizontal support required should be provided and same should be Fineshied with 1MM Laminate 1. 1NO X 4.67' X 8' ITEM TOTAL QUANTITY Sq.ft 37.33				
ITEM TOTAL QUANTITY Sq.ft 37.33	cabin with necessary teak wood beading. All the accessories used shall be concealed type. All the aluminium sections shall be powder coated with approved colour. The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading, fittings, hardware items, paintings, wood polish, rate etc. complete, Proper vertical & horizontal support required should be provided and same should be			
ITEM TOTAL QUANTITY Sq.ft 37.33	1 1NO Y 4 67' Y 9'			
		0 "	27.00	
	HEM TOTAL QUANTITY	Sq.ft	37.33	
5 CUSTOMER COUNTER TABLE	5 CUSTOMER COUNTER TABLE			

MANAGER CABIN: 1. 1NO X 10.5' X 10' 2. 1NO X 11.92' X 10' AT LOBBY & UPS AREA 1. 1NO X 5.16' X 2.5' ITEM TOTAL QUANTITY Sq.ft 237.08 MANAGER TABLES Providing and fixing TABLE of length 84", height 30" and top width 42" all minimum dimensions with front, working top and side supports. There shall be Two draws of size 13.5'% 22".5' fixed in a alround boxing with top and one of the side of the table as common top and side. The portion below the drawers shall have a cupboard with front shutter. All by using 19mm thick 'MR grade commercial board with exposed side with 1mm thick laminated finish except for draw bottom which shall be provided with 0 mm. MR grade commercial polywoodincluding providing and fixing 100mm 'C' type stainless steel handles, multipurpose locks, automatic steel Zero crank hinges for cupboards etc. The working top, sides, front face of draw shall be finished with exposed side with 1mm thick laminated finish. The working top shall be provided with 1mm thick claral gases edges biveled. For every seating area there shall be a key board tray of minimum 21" x 18" size made of 19mm thick 'MR grade commercial board with both side Imm thick laminated and fixed with telescopic type metal channels fixed on the lower side of the counter/table top. A foot rest of 3" x 2" Seasoned hard wood section with proper polishing. The draws shall have sliding arrangement by using readymade metal rollers in metal channel. All the exposed edges shall be provided with leak wood beadings of size 1" x .5" with proper polishing. The fire areas shall have sliding arrangement by using readymade metal rollers in metal channel. All the exposed edges shall be provided with leak wood beadings of size 1" x .5" with proper polishing. The fire his his provided inclusive of working top and covered with PVC caps as per Drawing. At every maximum of 5 ft .c'. main supports are provided for table and customer side covered upto table top with Commercial board over death PVC caps as per Drawing. At every maximum of 5 ft .c'. main	class quality hard wood frame at spacing not exceeding 3.0' c/c fixed to the bottom & ceiling. The Partition shall be skinned on both faces with 6 mm MR grade commercial plywood. of approved brand termite and water resistant. Exterior faces to be pasted with 1mm thick laminate of approved quality & Colour to the top & bottom Panels of the Partition, middle panel to be covered with 12mm thick plain glass fixed with necessary beedings, with itching of 5mm thick line at every 125mm c/c firmly fixed. The partition shall have 3 No. of Doors with Size 0.75m x 2.13m with Proper Hinges, Stoppers Locks, Handles, Hydraulic Closure etc., complete.Necessary openings must be made in the frame sections to run the wires, computer cables wherever necessary with PVC cap. Similarly necessary cuttings to be made in the partition to fix switch boxes of electrical, telephone sockets, computer Information outlets, making provision for laying conduit; The rate include Provision of extra frame work as necessary verticle and horizantal members to be taken upto RCC ceiling joined with a horizontal member at top and for skirting, etc. complete. The general main specification shall considered for design, elevation, specification ,make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading ,fittings, hardware items ,paintings, wood polish, rate etc. complete .			
2. 1NO X 11.92' X 10' AT LOBBY & UPS AREA 1. 1NO X 5.16' X 2.5' ITEM TOTAL QUANTITY Sq.ft 237.08 MANAGER TABLES Providing and fixing TABLE of length 84", height 30" and top width 42" all minimum dimensions with front, working top and side supports. There shall be Two draws of size 13.5"x 22"x 5" fixed in a alround boxing with top and one of the side of the table as common top and side. The portion below the drawers shall have a cupboard with front shutter. All by using 19mm thick 'MR grade commercial board with exposed side with 1mm thick laminated finish except for draw bottom which shall be provided with 6 mm MR grade commercial bylywood including providing and fixing 100mm 'C' type stainless steel handles, multipurpose locks, automatic steel Zero crank hinges for cupboards etc. The working top, sides, front face of draw shall be finished with exposed side with 1mm thick laminated finish. The working top shall be provided with 10mm thick clear glass edges biveled. For every seating area there shall be a key board tray of minimum 21" x 18" size made of 19mm thick 'MR grade commercial board with both side 1mm thick laminated and fixed with telescopic type metal channels fixed on the lower side of the counter/table top, A foot rest of 3" x 2" Seasoned hard wood section with proper polishing. The draws shall have sliding arrangement by using readymade metal rollers in metal channel. All the exposed edges shall be provided with teak wood beadings of size 1" x .5"with proper polishing. The hidden surfaces to be painted. Each draw shall have stainless steel handle with a locking system for the two draw unit. Necessary openings for the access of the wires with plug shall be provided inclusive of working top and covered with PVC caps as per Drawing. At every maximum of 6 ft of: c. main supports are provided for table and cusstomer side covered upto table top with Commercial boards used should be made of 19mm MR MR grade commercial board with both or single side side 1mm thick laminated finish, The general mai	MANAGER CABIN :			
AT LOBBY & UPS AREA 1. 1NO X 5.16' X 2.5' ITEM TOTAL QUANTITY Sq.ft 237.08 MANAGER TABLES Providing and fixing TABLE of length 84" ,height 30" and top width 42" all minimum dimensions with front , working top and side supports. There shall be Two draws of size 13.5''x 22" 5' fixed in a alround boxing with top and one of the side of the table as common top and side. The portion below the drawers shall have a cupboard with front shutter. All by using 19mm thick 'MR grade commercial board with exposed side with 16mm thick laminated finish except for draw bottom which shall be provided with 6 mm MR grade commercial plywood including providing and fixing 100mm 'C' type stainless steel handles, multipurpose locks, automatic steel Zero crank hinges for cupboards etc. The working top, sides front face of draw shall be finished with exposed side with 1mm thick laminated finish. The working top shall be a key board tray of minimum 21" x 18" size made of 19mm thick 'MR grade commercial board with both side 1mm thick clear glass edges biveled. For every seating area there shall be a key board tray of minimum 21" x 18" size made of 19mm thick 'MR grade commercial board with both side 1mm thick laminated and fixed with telescopic type metal channels fixed on the lower side of the counter/table top, A foot rest of 3" x 2" Seasoned hard wood section with proper polishing. The draws shall have sliding arrangement by using readymade metal rollers in metal channel. All the exposed edges shall be provided with with the wood beadings of size 1" x .5" with proper polishing. The hidden surfaces to be painted. Each draw shall have stainless steel handle with a locking system for the two draw unit. Necessary openings for the access of the wires with plug shall be provided inclusive of working top and covered with PVC caps as per Drawing. At every maximum of 5 ft c/c. main supports are provided for table and customers side covered upto table top with Commercial boards used should be made of 19mm MR grade commercial board with bo	1. 1NO X 10.5' X 10'			
ITEM TOTAL QUANTITY Sq.ft 237.08 MANAGER TABLES Providing and fixing TABLE of length 84", height 30" and top width 42" all minimum dimensions with front, working top and side supports. There shall be Two draws of size 13.5"x 22" x5" fixed in a alround boxing with top and one of the side of the table as common top and side. The portion below the drawers shall have a cupboard with front shutter. All by using 19mm thick 'MR grade commercial board with exposed side with 1mm thick laminated finish except for draw bottom which shall be provided with 6 mm MR grade commercial plywood including providing and fixing 100mm 'C' type stainless steel handles, multipurpose locks, automatic steel Zero crank hinges for cupboards etc. The working top, sides, front face of draw shall be finished with exposed side with 1mm thick laminated finish. The working top shall be provided with 10mm thick clear glass edges biveled. For every seating area there shall be a key board tray of minimum 21" x 18" size made of 19mm thick 'MR grade commercial board with both side 1mm thick laminated and fixed with telescopic type metal channels fixed on the lower side of the counter/table top, A foor test of 3" x 2" Seasoned hard wood section with proper polishing. The draws shall have sliding arrangement by using readymade metal rollers in metal channel. All the exposed edges shall be provided with teak wood beadings of size 1" x. 5" with proper polishing. The hidden surfaces to be painted. Each draw shall have stainless steel handle with a locking system for the two draw unit. Necessary openings for the access of the wires with plug shall be provided inclusive of working top and covered with PVC caps as per Drawing. At every maximum of 5 ft c/c. main supports are provided for table and cusstomer side covered upto table top with Commercial boards used should be made of 19mm MR grade commercial board with both or single side side 1mm thick laminated finish, The general main specification shall considered for design, elevation, specification,	2. 1NO X 11.92' X 10'			
MANAGER TABLES Providing and fixing TABLE of length 84", height 30" and top width 42" all minimum dimensions with front, working top and side supports. There shall be Two draws of size 13.5"x 22"x 5" fixed in a alround boxing with top and one of the side of the table as common top and side. The portion below the drawers shall have a cupboard with front shutter. All by using 19mm thick 'MR grade commercial board with exposed side with 1mm thick laminated finish except for draw bottom which shall be provided with 6 mm MR grade commercial plywood including providing and fixing 100mm 'C' type stainless steel handles, multipurpose locks, automatic steel Zero crank hinges for cupboards etc. The working top, sides, front face of draw shall be finished with exposed side with 1mm thick laminated finish. The working top shall be provided with 10mm thick clear glass edges biveled. For every seating area there shall be a key board tray of minimum 21" x 18" size made of 19mm thick 'MR grade commercial board with both side 1mm thick laminated finish. The working top shall be a level board with other side of the counter/table top, A foot rest of 3" x 2" Seasoned hard wood section with proper polishing. The draws shall have sliding arrangement by using readymade metal rollers in metal channel. All the exposed edges shall be provided with teak wood beadings of size 1" x .5" with proper polishing. The hidden surfaces to be painted. Each draw shall have stainless steel handle with a locking system for the two draw unit. Necessary openings for the access of the wires with plug shall be provided inclusive of working top and covered with PVC caps as per Drawing. At every maximum of 5 ft c/c. main supports are provided for table and customer side covered upto table top with Commercial boards used should be made of 19mm MR grade commercial board with both or single side side 1 mm thick laminated finish, The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items,	AT LOBBY & UPS AREA			
MANAGER TABLES Providing and fixing TABLE of length 84", height 30" and top width 42" all minimum dimensions with front, working top and side supports. There shall be Two draws of size 13.5" x2" x5" fixed in a alround boxing with top and one of the side of the table as common top and side. The portion below the drawers shall have a cupboard with front shutter. All by using 19mm thick 'MR grade commercial board with exposed side with 1mm thick laminated finish except for draw bottom which shall be provided with 6 mm MR grade commercial plywood. including providing and fixing 100mm 'C' type stainless steel handles, multipurpose locks, automatic steel Zero crank hinges for cupboards etc. The working top, sides.front face of draw shall be finished with exposed side with 1mm thick laminated finish. The working top shall be provided with 10mm thick clear glass edges biveled. For every seating area there shall be a key board tray of minimum 21" x 18" size made of 19mm thick 'MR grade commercial board with both side 1mm thick laminated and fixed with telescopic type metal channels fixed on the lower side of the counter/fable top, A foot rest of 3" x 2" Seasoned hard wood section with proper polishing. The draws shall have sliding arrangement by using readymade metal rollers in metal channel. All the exposed edges shall be provided with teak wood beadings of size 1" x .5" with proper polishing. The hidden surfaces to be painted. Each draw shall have stainless steel handle with a locking system for the two draw unit. Necessary openings for the access of the wires with plug shall be provided inclusive of working top and covered with PVC caps as per Drawing. At every maximum of 5 ft c/c. main supports are provided for table and customer side covered upto table top with Commercial boards used should be made of 19mm MR grade commercial board with both or single side side 1mm thick laminated finish, The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of item	1. 1NO X 5.16' X 2.5'			
Providing and fixing TABLE of length 84", height 30" and top width 42" all minimum dimensions with front, working top and side supports. There shall be Two draws of size 13.5"x 22". 5" fixed in a alround boxing with top and one of the side of the table as common top and side. The portion below the drawers shall have a cupboard with front shutter. All by using 19mm thick 'MR grade commercial board with exposed side with 1mm thick laminated finish except for draw bottom which shall be provided with 6 mm MR grade commercial plywood including providing and fixing 100mm 'C' type stainless steel handles, multipurpose locks, automatic steel Zero crank hinges for cupboards etc. The working top, sides, front face of draw shall be finished with exposed side with 1mm thick laminated finish. The working top shall be provided with 10mm thick clear glass edges biveled. For every seating area there shall be a key board tray of minimum 21" x 18" size made of 19mm thick 'MR grade commercial board with both side 1mm thick laminated and fixed with telescopic type metal channels fixed on the lower side of the counter/fable top, A foot rest of 3" x 2" Seasoned hard wood section with proper polishing. The draws shall have sliding arrangement by using readymade metal rollers in metal channel. All the exposed edges shall be provided with teak wood beadings of size 1" x .5" with proper polishing. The hidden surfaces to be painted. Each draw shall have stainless steel handle with a locking system for the two draw unit. Necessary openings for the access of the wires with plug shall be provided inclusive of working top and covered with PVC caps as per Drawing. At every maximum of 5 ft c/c. main supports are provided for table and cusstomer side covered upto table top with Commercial boards used should be made of 19mm MR grade commercial board with both or single side side 1mm thick laminated finish, The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material	ITEM TOTAL QUANTITY	Sq.ft	237.08	
Providing and fixing TABLE of length 84", height 30" and top width 42" all minimum dimensions with front, working top and side supports. There shall be Two draws of size 13.5"x 22" 5" fixed in a alround boxing with top and one of the side of the table as common top and side. The portion below the drawers shall have a cupboard with front shutter. All by using 19mm thick 'MR grade commercial board with exposed side with 1mm thick laminated finish except for draw bottom which shall be provided with 6 mm MR grade commercial plywood including providing and fixing 100mm 'C' type stainless steel handles, multipurpose locks, automatic steel Zero crank hinges for cupboards etc. The working top, sides, front face of draw shall be finished with exposed side with 1mm thick laminated finish. The working top shall be provided with 10mm thick clear glass edges biveled. For every seating area there shall be a key board tray of minimum 21" x 18" size made of 19mm thick 'MR grade commercial board with both side 1mm thick laminated and fixed with telescopic type metal channels fixed on the lower side of the counter/fable top, A foot rest of 3" x 2" Seasoned hard wood section with proper polishing. The draws shall have sliding arrangement by using readymade metal rollers in metal channel. All the exposed edges shall be provided with teak wood beadings of size 1" x .5" with proper polishing. The hidden surfaces to be painted. Each draw shall have stainless steel handle with a locking system for the two draw unit. Necessary openings for the access of the wires with plug shall be provided inclusive of working top and covered with PVC caps as per Drawing. At every maximum of 5 ft c/c. main supports are provided for table and cusstomer side covered upto table top with Commercial boards used should be made of 19mm MR grade commercial board with both or single side side 1mm thick laminated finish, The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material o	MANAGER TABLES			
2. 1NO X 4.58' X 2'	thick laminated finish except for draw bottom which shall be provided with 6 mm MR grade commercial plywood. including providing and fixing 100mm 'C' type stainless steel handles, multipurpose locks, automatic steel Zero crank hinges for cupboards etc. The working top, sides, front face of draw shall be finished with exposed side with 1mm thick laminated finish. The working top shall be provided with 10mm thick clear glass edges biveled. For every seating area there shall be a key board tray of minimum 21" x 18" size made of 19mm thick 'MR grade commercial board with both side 1mm thick laminated and fixed with telescopic type metal channels fixed on the lower side of the counter/table top, A foot rest of 3" x 2" Seasoned hard wood section with proper polishing. The draws shall have sliding arrangement by using readymade metal rollers in metal channel. All the exposed edges shall be provided with teak wood beadings of size 1" x .5"with proper polishing. The hidden surfaces to be painted. Each draw shall have stainless steel handle with a locking system for the two draw unit. Necessary openings for the access of the wires with plug shall be provided inclusive of working top and covered with PVC caps as per Drawing. At every maximum of 5 ft c/c. main supports are provided for table and cusstomer side covered upto table top with Commercial boards used should be made of 19mm MR grade commercial board with both or single side side 1mm thick laminated finish, The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading			
	2. 1NO X 4.58' X 2'	Sq.ft	35.42	
		•		
STORAGE UNITS				

	Providing and fixing storage units with necessary swinging shutters, all made of 19mm thick MR grade commercial board with both side 1mm thick laminated finish for sides, partitions, top, shelves, bottom, shutters. The exposed surfaces including rear side shall be finished with 1mm thick lamination of approved shade & brand. Unit shall have internally required horizontal shelves and vertical partitions all made with 19mm thick 'MR grade commercial board with both side 1mm thick laminated finish. All the exposed edges shall be lipped with1"x1/2" matching Wood Beading & neatly polished . All hidden surfaces shall be finished with paint. 12mm thick MR grade commercial plywood to be fixed for the rear side in side covered with 1 mm thick lamination finish. The shutters shall have locking arrangement , 3" size stainless steel handles, Ball catch,automatic steel Zero crank hinges for cupboards, 3" PC Aluminium Tower bolts as per the requirement. The general main specification shall considered for design,elevation,specification,make,colour,of items,quantity of items,material of items for commercial board,commercial ply wood, lamination,hard wood section,glass,beading ,fittings,hardware items ,paintings,wood polish, rate etc. complete . (DEPTH=18")			
	1. 1NO X 2' X 2.5'			
	2. 1NO X 3' X 2.5'			
	3. 1NO X 7' X 2.5'			
	4. 1NO X 5' X 2.5'			
	DEPTH 1'6" ITEM TOTAL QUANTITY	Sq.ft	42.50	
10	NOTICE BOARD			
	Providing and fixing notice board of size 4'x3' by using 19mm MR grade commercial board. All the exposed edges shall be lipped with1"x1/2" matching Wood Beading & neatly polished. The inside surface shall be provided with 12mm thick soft board with fabric on the top. remaining surfaces neatly painted. The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading ,fittings, hardware items ,paintings, wood polish, rate etc. complete.			
	1. 1NO X 4' X 3'			
	ITEM TOTAL QUANTITY	Sq.ft	12	
		Oq.it		
	CUSTOMER WRITING DESK Supplying and fixing free standing customer writing desk of 36" length, 42" height and 18" deep with top, front, side MS Angle supports and foot rest. There shall be bins of size 6" x6" (top opening) for keeping challans at the top level, shall have internally one horizontal shelf (9" DEPTH) with 5 wooden partition, all made out of 19mm thick 'MR grade commercial board of approved brand termite and water resistan1. The top, front and side exposed surfaces laminated with 1mm lamination and remaining surfaces neatly painted. All the exposed edges shall be lipped with 1"x1/2" matching Wood Beading & neatly polished, including MS angle support of size 35mm x 35mm x 4mm. The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading, fittings, hardware items, paintings, wood polish, rate etc. complete. depth= 9"			
	ITEM TOTAL QUANTITY	Sq.ft	4.5	
	Providing & fixing in position Flap Gate made out of 19mm thick `MR grade commercial board of approved brand termite and water resistant, The exposed surface to be covered with 1mm thick laminate of Approved shade & make. All the exposed edges shall be lipped with 1"x1/2" matching Wood Beading & neatly polished .The shutters shall have locking arrangement , 3" size brass or stainless steel handles, Continuous MS hinges, The Flap gate shall have with Proper Hinges, Stoppers Locks, Handles, etc.,The general main specification shall considered for design, elevation, specification , make, colour,of items,quantity of items,material of items for commercial board,commercial ply wood, lamination,hard wood section, glass,beading , fittings, hardware items ,paintings,wood polish, rate etc. complete .			
	1. 1NO X 3' X 2.5'			
	ITEM TOTAL QUANTITY	Sq.ft	7.50	
		• -		
13	SUGGESTION BOX			

1. 1NO X 1.5' X 1' ITEM TOTAL QUANTITY Sq.ft 1.50 14 VERTICAL BLINDS Providing and fixing of Luxaflex (of Hunter Douglas) / MAC make or equivalent brand window VERTICAL blinds. The top rail shall be made of powder coated aluminium section with best quality sliding arrangement. The general main specification shall considered for design,elevation,specification,make,colour,of items,quantity of items,material of items for	
Providing and fixing of Luxaflex (of Hunter Douglas) / MAC make or equivalent brand window VERTICAL blinds. The top rail shall be made of powder coated aluminium section with best quality sliding arrangement. The general main specification shall considered for design,elevation,specification,make,colour,of items,quantity of items,material of items for	
VERTICAL blinds. The top rail shall be made of powder coated aluminium section with best quality sliding arrangement. The general main specification shall considered for design,elevation,specification,make,colour,of items,quantity of items,material of items for	
commercial board,commercial ply wood, lamination,hard wood section,glass,beading ,fittings,hardware items ,paintings,wood polish, rate etc. complete .	
1. 5NO X 5.5' X 4.5'	
ITEM TOTAL QUANTITY Sq.ft 123.75	
Providing and fixing suspended false ceiling, which includes providing and fixing GI perimeter channels of size 0.55mm thick having one flange of 20mm and another flange of 30mm and a web of 27mm along with perimeter of ceiling, screw fixed to brick wall/partition with the help of nylon sleeves and screws at 610mm centers. The suspending GI intermediate channel of size 45mm, 0.9mm thick with two flanges of 15mm each from the soffit at 1220mm centers with ceiling angle of width 25mmx 10mmx 0.55mm thick fixed to soffit with GI cleat and steel expansion fastene. Ceiling section of 0.55mm thickness having knurled web of 51.5mm and two flanges of 26mm each with lips of 10.5mm are then fixed to the intermediate channel at 457mm centers. 12.5mm tapered edge Gypboard (Conforming to IS- 2095-1982) is then screwed fixed to ceiling section with 25mm dry wall screw at 230mm centers. Screw fixing is done mechanically. Finally the boards are to be jointed and finished so as to have a flush look which includes filling as finishing the tapered and square edge of the boards with joining compound, paper tape and two coats of primer suitable for Gypboard (as equivalent) extra frame work for electrical fittings, A/C diffusers, and/or any other cutout, trap doors, wooden shadow battens (hollock wood black enamel painted-25x40mm) at wall peripheries and ends, 12mm thick MDF board for pelmet etc. complete including opening to be made for AC grills, light fittings, trap doors etc. (Measurement shall be taken of the plan area only nothing extra for cove or verticle designs upto 9" height). (The quoted rate shall be inclusive of suspenders at all heights) (The rate to be quoted including plastic emulsion paint) The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading, fittings, hardware items, paintings, wood polish, rate etc. complete.	
ITEM TOTAL QUANTITY Sq.ft 125.13	
16 GLASS SHELF	
Providing & fixing glass planes of required size with all edges neatly grinded & polished and fixed to the wall surfaces using D brackets. The glass shall be 12mm thick plain glass of Modi, Saint Gobain make. The rate includes glass, fittings,hardware items ,paintings, labour etc. complete . 1. 3NO X 3' X 1.25'	
ITEM TOTAL QUANTITY Sq.ft 11.25	
TIEM TOTAL GOMETH	
17 CHECK DROP BOX NEAR CASH COUNTER	