BOQ FOR INTERIOR FURNISHING WORK AT KARNATAKA GRAMIN BANK, HEAD OFFICE, BALLARI.

GENERAL MAIN SPECIFICATION SHALL BE CONSIDERED FOR ALL ITEMS.

The Commercial boards used should be made of 19mm MR grade commercial board with both or single side 1mm thick laminated finish. Ply wood used for Storage unit rear side, partion wall inner and outer side and drawer and cupboard bottom which shall be provided with 6 mm MR grade commercial plywood with finish with 1mm thick laminate on one side per sheet. The boards and laminate make and colours for the counter, table top, vertical sides, drawer, cupboard, storage unit,bands, skirting ,partion wall customer writing table,Notice board, Suggestion box etc shall be strictly as per the recommended brand and colours indicated by Bank . The hidden surfaces to be painted with one coat of wood primer and two coats of enamel painting of approved colour and make of the paints. All the exposed edges shall be lipped with 1"X0.5" matching Teak Wood Beading & neatly polished with proper number of coats of melamine polish shall be provided Tables and counters shall be provided with required no of round holes of 2.5" size with PVC cap at the required location for wire management etc. complete. Tables and counters shall be provided with two drawers minimum size of 13.5"x 22"x 5" (internal dimensions) fixed in between the intermediate support and main support, at every maximum of 5 ft c/c. main supports are provided for each counter and cusstomer side covered upto table top with Commercial boards used should be made of 19mm MR grade commercial board with both or single side side 1mm thick laminated finish, the portion below the drawers shall have a cupboard with front shutter, providing and fixing 100mm 'C' type stainless steel handles, multipurpose locks, automatic steel Zero crank hinges for cupboards, the drawers to be provided with sliding channels etc. For every seating area tables and counters there shall be a key board tray of minimum 21" x 18" size made of 19mm MR grade commercial board with both side 1mm thick laminated and fixed with telescopic type metal channels fixed on the lower side of the counter/table top, For every seating area of tables and counters a foot rest of 3" x 2" Seasoned hard wood section with proper no of coats of melamine polish shall be provided on the lower side of the counter/table top. The front elevation of the counter, partition wall shall be as per the design detailed in the drawing or as detailed by the Architect/ Engineer in-charge using the front elevation of the counter / partion shall be as per the design detailed in the drawing using 6mm thick design teak wood/MDF material to provide recession and finished with 1mm laminate & 1mm thick laminate. Handles and other hardware items and other items have to be used as per banks approved list of material/ banks prior approval, etc.complete. The rate quoted should include cost and conveyance of all materials,labour for all items of work,HOM as per specification. rest of specifications same as MAIN specifications of all items, including tax, Complete to the satisfaction of the Engineer / Bank as per design/ drawing enclosed.

L NO	DESCRIPTION OF ITEM OF WORKS	UNIT	TOTAL QTY	RATE	AMOUNT
1	WOODEN CUM PARTITION FOR GM ROOM, CM ROOM, CONFERENCE HALL, SERVER ROOM, PANTRY & CUBICAL PARTITION:				
	Providing, Fabricating & Fixing Partition frame consisting of 2.5"x2.5" well seasoned first class quality hard wood frame at spacing not exceeding 3.0' c/c fixed to the bottom & ceiling. The Partition shall be skinned on both faces with 6 mm MR grade commercial plywood of approved brand termite and water resistant. Exterior faces to be pasted with 1mm thick laminate of approved quality & Colour to the top & bottom Panels of the Partition, middle panel to be covered with 12mm thick plain glass fixed with necessary beedings, with itching of 5mm thick line at every 125mm c/c firmly fixed. for cubical partition 4' height bottom panel only. The partition shall have 2 Doors with Size 0.9m x 2.13m with Proper Hinges, Stoppers Locks, Handles, Hydraulic Closure etc., complete.Necessary openings must be made in the frame sections to run the wires, computer cables wherever necessary with PVC cap. Similarly necessary cuttings to be made in the partition to fix switch boxes of electrical, telephone sockets, computer Information outlets, making provision for laying conduit; The rate include Provision of extra frame work as necessary verticle and horizantal members to be taken upto RCC ceiling joined with a horizontal member at top and for skirting, etc. complete. The general main specification shall considered for design, elevation, specification ,make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading ,fittings, hardware items ,paintings, wood polish, rate etc. complete .				
	ITEM TOTAL QUANTITY	Sq.ft	2683.83		
2	CUBICAL WORKING TABLE				
	Providing and fixing CUBICAL WORKING TABLE of total height 30" and working top width of 30" width (all minimum dimensions) all as per drawing with front, working top, main vertical support upto the working top at every maximum of 5 ft c/c and intermediate vertical support for draw unit upto working top. The working top shall be at a height of 30". There shall be two drawers of size 14"x 22"x 5" (internal dimensions) The portion below the drawers shall have a cupboard with front shutter. The counter and the drawers shall be made by using 19mm thick 'MR grade commercial board with Out side 1mm thick laminated finish except for draw bottom which shall be provided with 6 mm MR grade plywood. The Cubical working table top, front face of shutter and draw shall be finished with 1 mm thick lamination. For every seating area (normally 4' to 5 feet length) there shall be a key board tray of minimum 21" x 18" size made of 19mm MR grade commercial board with top side 1 mm thick laminated and fixed with telescopic type metal channels fixed on the lower side of the table top, a foot rest made of 3" x 2" seasoned hard wood section with proper polish. The drawers to be provided with sliding channels including fixing keyboard with telescopic sliding channel. All the exposed edges shall be provided with teak wood beadings of size 1" x .5" with proper polish. The hidden surfaces to be painted. Each drawer/cupboard shall including providing and fixing 100mm 'C' type stainless steel handles, Godrej multipurpose locks, automatic steel Zero crank hinges for cupboards etc. Necessary openings for the access of the wires with plug shall be provided with PVC caps for the counter top at appropriate location. At every maximum of 5 ft c/c. main supports are provided for each counter and cusstomer side covered upto table top with Commercial boards used should be made of 19mm MR grade commercial board with both or single side side 1mm thick laminated finish, The general main specification shall considered for design, elevation, specification,				

3	TABLE FOR GM ROOMS, CM ROOMS			
	Providing and fixing TABLE of length 84", height 30" and top width 42" all			
	minimum dimensions with front, working top and side supports. There shall be Two draws of size 16"x 22"x 5" fixed in a alround boxing with top and one of the			
	side of the table as common top and side. The portion below the drawers shall			
	have a cupboard with front shutter. All by using 19mm thick `MR grade			
	commercial board with exposed side with 1mm thick laminated finish except for			
	draw bottom which shall be provided with 6 mm MR grade commercial plywood			
	including providing and fixing 100mm 'C' type stainless steel handles, multipurpose			
	locks, automatic steel Zero crank hinges for cupboards etc. The working top,			
	sides, front face of draw shall be finished with exposed side with 1mm thick			
	laminated finish. The working top shall be provided with 10mm thick clear glass			
	edges biveled. For every seating area there shall be a key board tray of minimum			
	21" x 18" size made of 19mm thick `MR grade commercial board with both side			
	1mm thick laminated and fixed with telescopic type metal channels fixed on the			
	lower side of the counter/table top, A foot rest of 3" x 2" Seasoned hard wood			
	section with proper polishing. The draws shall have sliding arrangement by using			
	readymade metal rollers in metal channel. All the exposed edges shall be provided			
	with teak wood beadings of size 1" x .5"with proper polishing . The hidden surfaces			
	to be painted. Each draw shall have stainless steel handle with a locking system			
	for the two draw unit. Necessary openings for the access of the wires with plug shall be provided inclusive of working top and covered with PVC caps as per Drawing.			
	At every maximum of 5 ft c/c. main supports are provided for table and cusstomer			
	side covered upto table top with Commercial boards used should be made of 19mm			
	MR grade commercial board with both or single side side 1mm thick laminated			
	finish, The general main specification shall considered for			
	design,elevation,specification,make,colour,of items,quantity of items,material of			
	items for commercial board,commercial ply wood, lamination,hard wood			
	section,glass,beading ,fittings,hardware items ,paintings,wood polish, rate etc.			
	complete .			
	ITEM TOTAL QUANTITY	Sq.ft	170.00	
4	TABLE FOR CONFERENCE ROOMS			
	Providing and fixing TABLE of length 11' ,height 30" and top width 4' all minimum			
	dimensions with front, working top and side supports. The working top, sides			
	shall be finished with exposed side with 1mm thick laminated finish. The working			
	top shall be provided with 10mm thick clear glass edges biveled. For every seating			
	area there shall be a key board tray of minimum 21" x 18" size made of 19mm thick			
	`MR grade commercial board with both side 1mm thick laminated and fixed with telescopic type metal channels fixed on the lower side of the counter/table top. A			
	foot rest of 3" x 2" Seasoned hard wood section with proper polishing. All the			
	exposed edges shall be provided with teak wood beadings of size 1" x .5"with proper			
	polishing . The hidden surfaces to be painted. Necessary openings for the			
	access of the wires with plug shall be provided inclusive of working top and covered			
	with PVC caps as per Drawing. main supports are provided for table at required			
	locations with both side 1mm thick laminated. The general main specification shall			
	considered for design, elevation, specification, make, colour, of items, quantity of			
	items,material of items for commercial board,commercial ply wood, lamination,hard			
	wood section, glass,beading, fittings,hardware items,paintings,wood polish, rate			
	etc. complete .			
	ITEM TOTAL QUANTITY	Sq.ft	44.00	

5	MINERAL FIRRE ROARD GRID TYPE FALSE CEILING			
5	MINERAL FIBRE BOARD GRID TYPE FALSE CEILING Providing, fabricating, erecting lay-intype tegular/droptype Mineral fibre board false Ceiling of 600mmx600mm grid asper the following specifications. The approved brands are ARMSTRONG or Tiles of Saint Gobain Mineral Fibre Acoustic Ceiling Tiles. The following specifications are the minimum and tenderers may quote for the equivalent or better specification. The grid system having 600 mm x 600 mm or part there of wherever necessary, shall be made using hot dipped galvanized steel section, exposed surface chemically cleaned capping prefinished in backed polyester paint, main Tee of size 14 x 38 x 0.33 mm at every 1200 mm c/c max and rotary stitched cross tee of size 14 x 38 x 0.33 mm at every 600 mm c/c and cross Tee of size 14 x 38 x 0.33 mm at every 1200 c/c max and 14 x 22 x 0.457 mm wall angle alround the wall to form grid size of 600 x 600 mm. The suspension system shall have 4mm dia pre straightened GI rods which are in-turn supported from real ceiling using 6 mm size anchor bolts, connected with adjustable Hanger clips / Jbolts and other accessories as per the manufacturers specifications. The T			
	Sections have a Galvanizing of 120 grams per M2 & passed through for 500 hrs of Salt test. The tiles/panels shall be of prima Fine Fissured Microlook tegular of ARMSTRONG Mineral Fibre Acoustic CeilingTiles of size 600 x 600 x 18 mm thick over the formed grid, in module size of 600 mm x 600 mm x 18mm Thick. The item shall include the cost of additionalTee or L supports & other accessories near the ends / odd size edges / corners, making necessary openings for electrical light fittings, fire alarm detectors and any other fixtures. No extra payement shall be made for making openings in the panels / grid for the purpose of light fittings. Item rate shall include all the taxes, transporation, erection, loading & unloading and any other incidental expenditure that may be required to be spent in completing the work in totality as per above specifications. The tiles removed to place light fittings shall be handed over to bank's custody and there may not be any deduction for light fittings area.			
	ITEM TOTAL QUANTITY	Sq.ft	3795.00	
		Sq.ft	3795.00	
6	STORAGE UNITS FOR GM ROOMS & CM ROOMS	Sq.ft	3795.00	
6			3795.00	
6	STORAGE UNITS FOR GM ROOMS & CM ROOMS Providing and fixing storage units with necessary swinging shutters, all made of 19mm thick MR grade commercial board with both side 1mm thick laminated finish for sides, partitions, top, shelves, bottom, shutters. The exposed surfaces including rear side shall be finished with 1mm thick lamination of approved shade & brand. Unit shall have internally required horizontal shelves and vertical partitions all made with 19mm thick 'MR grade commercial board with both side 1mm thick laminated finish. All the exposed edges shall be lipped with1"x1/2" matching Wood Beading & neatly polished . All hidden surfaces shall be finished with paint. 12mm thick MR grade commercial plywood to be fixed for the rear side in side covered with 1 mm thick lamination finish. The shutters shall have locking arrangement , 3" size stainless steel handles, Ball catch,automatic steel Zero crank hinges for cupboards, 3" PC Aluminium Tower bolts as per the requirement. The general main specification shall considered for design,elevation,specification,make,colour,of items,quantity of items,material of items for commercial board,commercial ply wood, lamination,hard wood section,glass,beading ,fittings,hardware items ,paintings,wood		3795.00	
6	STORAGE UNITS FOR GM ROOMS & CM ROOMS Providing and fixing storage units with necessary swinging shutters, all made of 19mm thick MR grade commercial board with both side 1mm thick laminated finish for sides, partitions, top, shelves, bottom, shutters. The exposed surfaces including rear side shall be finished with 1mm thick lamination of approved shade & brand. Unit shall have internally required horizontal shelves and vertical partitions all made with 19mm thick 'MR grade commercial board with both side 1mm thick laminated finish. All the exposed edges shall be lipped with1"x1/2" matching Wood Beading & neatly polished . All hidden surfaces shall be finished with paint. 12mm thick MR grade commercial plywood to be fixed for the rear side in side covered with 1 mm thick lamination finish. The shutters shall have locking arrangement , 3" size stainless steel handles, Ball catch,automatic steel Zero crank hinges for cupboards, 3" PC Aluminium Tower bolts as per the requirement. The general main specification shall considered for design,elevation,specification,make,colour,of items,quantity of items,material of items for commercial board,commercial ply wood, lamination,hard wood section,glass,beading ,fittings,hardware items ,paintings,wood polish, rate etc. complete . (DEPTH=18")			
6	STORAGE UNITS FOR GM ROOMS & CM ROOMS Providing and fixing storage units with necessary swinging shutters, all made of 19mm thick MR grade commercial board with both side 1mm thick laminated finish for sides, partitions, top, shelves, bottom, shutters. The exposed surfaces including rear side shall be finished with 1mm thick lamination of approved shade & brand. Unit shall have internally required horizontal shelves and vertical partitions all made with 19mm thick `MR grade commercial board with both side 1mm thick laminated finish. All the exposed edges shall be lipped with1"x1/2" matching Wood Beading & neatly polished. All hidden surfaces shall be finished with paint. 12mm thick MR grade commercial plywood to be fixed for the rear side in side covered with 1 mm thick lamination finish. The shutters shall have locking arrangement, 3" size stainless steel handles, Ball catch, automatic steel Zero crank hinges for cupboards, 3" PC Aluminium Tower bolts as per the requirement. The general main specification shall considered for design, elevation, specification, make, colour, of items, quantity of items, material of items for commercial board, commercial ply wood, lamination, hard wood section, glass, beading, fittings, hardware items, paintings, wood polish, rate etc. complete. (DEPTH=18")			
6	STORAGE UNITS FOR GM ROOMS & CM ROOMS Providing and fixing storage units with necessary swinging shutters, all made of 19mm thick MR grade commercial board with both side 1mm thick laminated finish for sides, partitions, top, shelves, bottom, shutters. The exposed surfaces including rear side shall be finished with 1mm thick lamination of approved shade & brand. Unit shall have internally required horizontal shelves and vertical partitions all made with 19mm thick 'MR grade commercial board with both side 1mm thick laminated finish. All the exposed edges shall be lipped with1"x1/2" matching Wood Beading & neatly polished . All hidden surfaces shall be finished with paint. 12mm thick MR grade commercial plywood to be fixed for the rear side in side covered with 1 mm thick lamination finish. The shutters shall have locking arrangement , 3" size stainless steel handles, Ball catch,automatic steel Zero crank hinges for cupboards, 3" PC Aluminium Tower bolts as per the requirement. The general main specification shall considered for design,elevation,specification,make,colour,of items,quantity of items,material of items for commercial board,commercial ply wood, lamination,hard wood section,glass,beading ,fittings,hardware items ,paintings,wood polish, rate etc. complete . (DEPTH=18") ITEM TOTAL QUANTITY			